

## Accurate

The L75-SE document reader is a professional and innovative cheque reader that extends the range of supported documents with its MICR and/or OCR reading capability.

L75-SE hand reader is designed to fulfill Teller's and Retail's exigencies. It is particularly suited for the replacement of older check reader models thanks to

the availability of several of the most popular cheque reading application interfaces. Its friendly design and automatic drop and feed mechanism (pinch

# **Foolproof**

Small footprint - only 88mm in width and 200mm in lenght

roller) make it very simple and straightforward to use.

### Compact

- Professional reader quiet and reliable guarantee maximum workstation productivity with minimal human intervention
- Easy-fitting for different applications used by leading financial and government institutions

The L75-SE comes with USB interface and an external power supply and may be equipped with a magnetic stripe swipe card reader, a storage pocket for up to 60 documents, and a document input holder to ease document introduction, as additional options.









### Small size, big quality

High performance and accuracy in MICR reading, CMC7 and E13B. Automatic format detection between CMC7 and E13B. OCR code line reader (OCR A, OCR B, E13B). Proprietary DLL and certified drivers under all Windows operating systems.

#### **Basic unit features**

- · Single feed document reader
- MICR (CMC7/E13B) reader Conforming to ISO STD 1004 Reading height: 11 mm Reading centre line: 8 mm
- · OCR code line reader:

OCR A, OCR B (ISO STD 1073 I/II) and E13B

Combinations of OCR and E13B characters on the same code line,

separated by an "X"

Read head height (scan field): 12.7 mm Reading centre line: 8.5 or 19 mm Recognition with neuronal technology (ICR)

#### **Options**

- 60 documents storage bin
- Magnetic stripe card swipe reader, track 1&2, 2&3, 1&2&3
- RS232 connection (150 ÷ 38400 baud)

#### **Document specifications**

- Height: 30 ÷ 110 mm / 1.2 ÷ 4.33 in
- Length: 80 ÷ 216 mm / 3.15 ÷ 8.5 in
- Weight: 70 ÷ 120 gr/sqm / 0.01 ÷ 0.02 lb/sqf

#### **Connection interface**

• USB 2.0 (High Speed)

#### **Performance**

• 2500 docs/h

#### **Power supply**

- External switching adapter
- Input: 100-240 Vac ±10%, 50-60 Hz
- Output: 15 Vdc, 18W
- ON/OFF Switch on the reader

#### **Homologation**

- CE, CSA C & US, FCC
- EN60950

#### Size & weight

- Dimensions: 103 mm / 4.06 in (H); 88 mm / 3.46 in (W); 200 mm / 7.87 in (L) or length 425mm / 16.7 in (with the optional storage bin);
- Weight: 1.5 kg / 3.3 lb







CTS electronics Corso Vercelli, 332 10015 - Ivrea (TO) - Italy Phone: +39-0125-235611 www.ctsgroup.it

#### **About CTS electronics**

Since 1980, CTS has been a leading manufacturer of cash and cheque solutions with over 1.000.000 banking peripherals across five continents.

Our expertise includes: Document Processing Devices, Card Personalization Printers, OEM Modules and Dispensers, Cash and Coin Recycling and Processing Systems.